

		BASIC	
		项目号	G112-I11
Code			2T0032300812
Factory model			EU-KFR26GW/BP2N1Y-R1U(RC4)-W
Indoor code			220032308660
Indoor unit factory model			EU-KFR26G/BP2N1Y-R1U(RC4)-W
Outdoor code			220037306110
Outdoor unit factory model			EU-KFR26W/BP3N1-110(RC4)-W
Model			MSR1U-09HRDN1-QRC4W
Indoor			MSR1U-09HRDN1-QRC4W
Outdoor			MOB-09HFN1-QRC4W
Pdesignc	kW		2.7
SEER			5.5
Energy class			A
Pdesignh	kW		2.9
SCOP			3.4
Energy class			A
Tbiv	°C		-7
Tol	°C		-15
Power supply		Ph-V-Hz	220-240V~ 50Hz, 1Ph
Rated Cooling	Capacity	kW	0.82-2.64-3.37
	Input	W	180-910-1290
	Rated current	A	4.0
	Rated EER	W/W	2,90
Rated Heating	Capacity	kW	0.82-2.64-3.46
	Input	W	170-920-1210
	Rated current	A	4.0
	Rated COP	W/W	2,90
Moisture Removal		L/h	1.0
Max. input consumption		W	2000
Max. current		A	9.0
Starting current		A	----
Compressor	Model		DA108X1C-23EZ
	Type		ROTARY
	Brand		GMCC
	Capacity	Btu/h	11021
	Input	W	855
	Rated current(RLA)	A	4.95
	Locked rotor Amp(LRA)	A	----
	Thermal protector		----
	Thermal protector position		----
	Capacitor	uF	----
Refrigerant oil/oil charge	ml	ESTER OIL VG74 480ml	
Indoor fan motor	Model		RPG13H
	Brand		Welling
	Input	W	34
	Capacitor	uF	1.2
	Speed(Hi/Mi/Lo)	r/min	1100 / 950 / 870
a.Number of rows			2

Indoor coil	b.Tube pitch(a)x row pitch(b)	mm	20x11.28
	c.Fin spacing	mm	1.3
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ6,innergroove tube
	f.Coil length x height x width	mm	540x240x22.56
	g.Number of circuits		2
	Indoor air flow (Hi/Mi/Lo)		m3/h
Indoor sound power noise level (Hi)		dB(A)	53
Indoor sound pressure noise level ( Hi/Mi/Lo)		dB(A)	36/ 32/28
Indoor unit	Dimension(W*D*H)	mm	710x189x250
	Packing (W*D*H)	mm	775x260x324
	Net/Gross weight	Kg	6.5 / 8.5
Outdoor fan motor	Model		WZDK35-38G
	Brand		Panasonic
	Output	W	35
	Capacitor	uF	6.0
	Speed	r/min	850 / /
Outdoor coil	a.Number of rows		1
	b.Tube pitch(a)x row pitch(b)	mm	25.4x22
	c.Fin spacing	mm	1.6
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ9.52,innergroove tube
	f.Coil length x height x width	mm	754x508x22
	g.Number of circuits		2
Outdoor air flow		m3/h	1800
Outdoor sound power noise level		dB(A)	62
Outdoor sound pressure noise level		dB(A)	52
Outdoor unit	Dimension(W*D*H)	mm	780x250x540
	Packing (W*D*H)	mm	910x335x585
	Net/Gross weight	Kg	29.5 / 31.5
Refrigerant type		g	R410A/700g
Design pressure		MPa	4.2/1.5
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Φ6.35/Φ9.52(1/4"/3/8")
	Max. refrigerant pipe length	m	20
	Max. difference in level	m	8
Connection wiring			1.5(Optional)
Plug type			--
Thermostat type			Remote Control
Operation temperature	Indoor(cooling/ heating)	℃	≥17/≤30
	Outdoor(cooling/heating)	℃	0~50/-15~30
Application area		m2	13-22
Qty/per 20' /40' /40'HQ			117/251/276





